CLEAN-OUT PLUG WITH RAISED NUT WATERTIGHT SCREW PLUG, MPT · 2' MAX -30" FINISHED GRADE 4" 8" **I** 5" <u>ITT</u> <u>ITT</u> 30"x30"x8" 18" MIN. CONCRETE PAD 4" MIN. STRONG BACK CLEAN-OUT ADAPTER, SPxFPT FERNCO PVC ASTM 3034, MIN. 2% SLOPE P-TRAP, HUBxHUB PROFILE NOTES: 1. TRAILER DUMP CONNECTION ONLY ALLOWED WHEN AUTHORIZED BY THE DISTRICT. 2. ALL PIPE SHALL BE ABS, SCHEDULE 40, SOLVENT WELD UNLESS OTHERWISE NOTED. 2. ALL FITTINGS SHALL BE ABS, HUBxHUB. 3. TRANSITION FROM ABS PIPE TO PVC PIPE SHALL BE MADE WITH A STRONG BACK FERNCO COUPLING ADAPTER. TRAILER DUMP NOT TO SCALE **DETAIL APPROVALS** NORTHSHORE UTILITY DISTRICT 18 EDITOR ТМС 2022 STANDARD SEWER DETAILS LAST UPDATED FEBRUARY 2020 MANAGER SJD