



NOTES:

1. ANY MODIFICATION OR REPAIR TO A SIDE SEWER REQUIRES A PERMIT. PERMIT APPLICATIONS AND HOW TO APPLY CAN BE FOUND ON NORTHSORE UTILITY DISTRICT'S WEBSITE, [HTTPS://WWW.NUD.NET/PERMITS-CONSTRUCTION/PERMIT-SERVICES-INSPECTIONS/](https://www.nud.net/permits-construction/permit-services-inspections/)
2. REPAIRS ON EXISTING PVC SIDE SEWER PIPE REQUIRE THE USE OF GASKETED PVC REPAIR COUPLERS. SIDE SEWER REPAIRS THAT CONNECT PVC TO DISSIMILAR PIPE (E.G. CONCRETE, DUCTILE IRON, CLAY) TO USE STRONGBACK RC 1000 SERIES FERNCOS. A ROMAC COUPLER IS REQUIRED WHEN CONNECTING TO THE DISTRICT OWNED 6" STUB PER STANDARD SEWER DETAIL 8a.

TYPICAL PRIVATE SIDE SEWER REPAIR

NOT TO SCALE

DETAIL APPROVALS

EDITOR TMC

ENG. DIR. CF

NORTHSORE UTILITY DISTRICT

2025 STANDARD SEWER DETAILS

8d

LAST UPDATED
MAY 2025