



- 4" GATE VALVE, FLxFL.
- 4" COMPANION FLANGE WITH 2" IPS TAP.
- 2"x4" GALVANIZED IRON PIPE NIPPLE.
- 2" 90° GALVANIZED ELBOW, FIPxFIP.
- 2" STREET ELBOW, FIPxMIP
- 2" GALVANIZED IRON PIPE, LENGTH TO FIT.
- 2" BRASS COUPLING, FIPxFIP.
- 2" PVC PLUG.
- TWO-PIECE CAST IRON VALVE BOX AND ETHAFOAM RING PER THE SPECIFICATIONS AND STANDARD WATER DETAIL 11.
- TRACER WIRE: BLUE 14 GAUGE COPPER, CONTINUOUS, SOLID CORE, POLYETHYLENE INSULATED PER THE SPECIFICATIONS. CONTINUOUS FROM MAINLINE.
- (M)ARMORCAST METER BOX, A6001640PCX12-NUD (WITH NO "MOUSE HOLES") AND ARMORCAST COVER, A6001947T-NUD, OR DFW METER BOX, DFW1730CNP4-12-BODY AND DFW COVER DFW1730C-4M-BLANK-NS-NHK-LID.

BLOW-OFF ASSEMBLY

DETAIL APPROVALS

EDITOR TMC MANAGER SJD

NORTHSHORE UTILITY DISTRICT

2022 STANDARD WATER DETAILS



APRIL 2021